Sun Xtender PVX-9150T

Solar Battery Manufactured by: Concorde Battery Corporation

Description of Solar Battery:

VRLA-AGM Deep Cycle Battery for Off Grid and Grid Tied Systems.

Sun Xtender pioneered renewable energy storage batteries for Off Grid and Grid Tied Systems.

Since 1987, Sun Xtender has been designing valve regulated lead acid batteries with AGM construction (VRLA-AGM).The non-spillable construction allows the battery to be used upright or on its end or side and the maintenance free AGM design means no water replenishment ever.

Utilizing pure lead calcium grids, the plates are thicker than the industry standard for longer cycle life, increased reliability and power. The low impedance AGM design allows for excellent charge acceptance and there is no current limit required with controlled voltage charging.

The Sun Xtender product line features proprietary PolyGuard[™] Microporous Polyethylene Separators, shielding the positive plates against shorting, shock or vibration. No other manufacturer offers this dual layer of insulation protection.

Sun Xtender battery covers and containers are uniquely molded with high impact, reinforced copolymer polypropylene and are designed with thick end walls to prevent bulging. The copper alloy T Terminals are corrosion resistant and are supplied with silicon bronze bolts and washers.

All Sun Xtender Batteries ship Hazmat EXEMPT.

See the Sun Xtender Battery Technical Manual for details on applications and specifications.

PVX-9150T

Voltage						2v						
Battery Series					2 Volt Sun Xtender Series							
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 Volts per cell - 24 Hour Rate					915 Ah							
Weight 94 lb / 42.6 kg												
Sun Xtender® Solar			Ler	ngth	Width		Heig		ght			
Battery Part Number			in	mn	mm		mn	n in		mm		
PVX-9150T			10.2	28 261 7		. 06179		9 12.94	. 3	328.6		
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell												
1 Hr	2 Hr	4 Hr	8 Hr	24 H	24 Hr		łr	72 Hr	1	20 Hr		
Rate	Rate	Rate	Rate	Rate	3	Rate		Rate	F	Rate		
570 Ah	735 Ah	810 Ah	840 Ah	915 A	h	1005 /	4h	1044 Ah	10	1074 Ah		

Specifications subject to change without notice.



Renewable Energy Battery Applications

- Off Grid Homes
- Area Lighting: Street, Parking Lot, Transit Shelter Solar Security Lighting
- Arrow & Message Boards for Highway Traffic Control Employing Solar Modules
- SCADA (Supervisory Control
- & Data Acquisition) Systems
- Cathodic Protection Systems
- Grid Tied Solar Homes

