
8G24UT-DEKA

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	84.5Ah
Capacity at C/20	73.6Ah
Weight	52 lbs. (23.6 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) - 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35VPC
Float	2.25 - 2.30VPC
Vent	Self-sealing (2 PSI operation)
Electrolyte	Sulfuric acid thixotropic gel
Terminal	G (T881)



Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co, Inc.


Distributed by:

Valve-Regulated, Gelled-Electrolyte Battery



DIMENSIONS

Length (mm)	**10.875 (276 mm)**
Width (mm)	**6.75 (171 mm)**
Height (mm)	**9.25 (235 mm)**



MK Battery

1631 South Sinclair Street ● Anaheim, California 92806

Toll Free: 800-372-9253 ● Fax: 714-937-0818 ● E-mail: sales@mkbattery.com