



IQ8MC Microinverter


Our newest IQ8 Series Microinverters are the industry's first microgrid-forming*, software-defined microinverters with split-phase power conversion capability to convert DC power to AC power efficiently. The brain of the semiconductor-based microinverter is our proprietary application-specific integrated circuit (ASIC), which enables the microinverter to operate in grid-tied or off-grid modes. This chip is built in advanced 55-nm technology with high-speed digital logic and has superfast response times to changing loads and grid events, alleviating constraints on battery sizing for home energy systems.



Part of the Enphase Energy System, IQ8 Series Microinverters integrate with the IQ Battery, IQ Gateway, and the Enphase App monitoring and analysis software.



IQ8 Series Microinverters redefine reliability standards with more than one million cumulative hours of power-on testing, enabling an industry-leading limited warranty of up to 25 years.



Connect PV modules quickly and easily to the IQ8 Series Microinverters that have integrated MC4 connectors.



IQ8 Series Microinverters are UL Listed as PV rapid shutdown equipment and conforms with various regulations when installed according to the manufacturer's instructions.

Easy to install

- Lightweight and compact with plug-and-play connectors
- Power line communication (PLC) between components
- Faster installation with simple two-wire cabling

High productivity and reliability

- Produces power even when the grid is down*
- More than one million cumulative hours of testing
- Class II double-insulated enclosure
- Optimized for the latest high-powered PV modules

Microgrid-forming

- Complies with the latest advanced grid support
- Remote automatic updates for the latest grid requirements
- Configurable to support a wide range of grid profiles
- Meets CA Rule 21 (UL 1741-SA) and IEEE 1547:2018 (UL 1741-SB)

NOTE:

- IQ8 Microinverters cannot be mixed together with previous generations of Enphase microinverters (IQ7 Series, IQ6 Series, etc.) in the same system.
- IQ Gateway is required to change the default grid profile at the time of installation to meet the local Authority Having Jurisdiction (AHJ) requirements.

IQ8MC Microinverter

INPUT DATA (DC)		UNITS	IQ8MC-72-M-US			
Commonly used module pairings ¹		W	260–460			
wModule compatibility			To meet compatibility, PV modules must be within the following max. input DC voltage and max. module I _{sc} Module compatibility can be checked at https://enphase.com/installers/microinverters/calculator .			
MPPT voltage range		V	25–45			
Operating range		V	18–58			
Min./Max. start voltage		V	22/58			
Max. input DC voltage		V	60			
Max. continuous operating DC current		A	14			
Max. input DC short-circuit current		A	25			
Max. module I _{sc}		A	20			
Overvoltage class DC port			II			
DC port backfeed current		mA	0			
PV array configuration			Ungrounded array; no additional DC side protection required; AC side protection requires max 20 A per branch circuit			
OUTPUT DATA (AC)		UNITS	IQ8MC-72-M-US @240 VAC		IQ8MC-72-M-US @208 VAC	
Peak output power		VA	330		315	
Max. continuous output power		VA	320		310	
Nominal grid voltage (L-L)		V	240, split-phase (L-L), 180°		208, single-phase (L-L), 120°	
Min./Max. grid voltage ²		V	211–264		183–229	
Max. continuous output current		A	1.33		1.49	
Nominal frequency		Hz	60			
Extended frequency range		Hz	47–68			
AC short circuit fault current over three cycles		A _{rms}	2.70			
Max. units per 20 A (L-L) branch circuit ³			12		10	
Total harmonic distortion		%	<5			
Overvoltage class AC port			III			
AC port backfeed current		mA	18			
Power factor setting			1.0			
Grid-tied power factor (adjustable)			0.85 leading ... 0.85 lagging			
Peak efficiency		%	97.4		97.2	
CEC weighted efficiency		%	97.0		96.5	
Nighttime power consumption		mW	33		25	
MECHANICAL DATA		UNITS				
Ambient temperature range		–40°C to 65°C (–40°F to 149°F)				
Relative humidity range		4% to 100% (condensing)				
DC connector type		Stäubli MC4				
Dimensions (H × W × D); Weight		212 mm (8.3") × 175 mm (6.9") × 30.2 mm (1.2"); 1.1 kg (2.43 lbs)				
Cooling		Natural convection – no fans				
Approved for wet locations; Pollution degree		Yes; PD3				
Enclosure		Class II double-insulated, corrosion-resistant polymeric enclosure				
Environ. category; UV exposure rating		NEMA Type 6; outdoor				
COMPLIANCE						
Certifications	CA Rule 21 (UL 1741-SA), UL 62109-1, IEEE 1547:2018 (UL 1741-SB), FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 NO. 107.1-01 This product is UL Listed as PV rapid shutdown equipment and conforms with NEC 2014, NEC 2017, NEC 2020, and NEC 2023 section 690.12 and C22.1-2018 Rule 64-218 rapid shutdown of PV systems for AC and DC conductors when installed according to the manufacturer’s instructions.					

(1) No enforced DC/AC ratio.

(2) Nominal voltage range can be extended beyond nominal if required by the utility.

(3) Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

Revision history

REVISION	DATE	DESCRIPTION
DSH-00049-3.0	October 2023	Included NEC 2023 specification in the Compliance section.
DSH-00049-2.0	September 2023	Updated module compatibility information.
DSH-00049-1.0	May 2023	Preliminary release.