

# Enphase IQ Combiner

(X-IQ-AM1-240-B)

The **Enphase IQ Combiner™** with Enphase IQ Envoy™ consolidates interconnection equipment into a single enclosure and streamlines PV installations by providing a consistent, pre-wired solution for residential applications.



## Smart

- Includes IQ Envoy for communication and control
- Flexible networking supports Wi-Fi, Ethernet, or cellular

## Simple

- Three pre-installed 20 A / 240 VAC circuit breakers
- Provides production metering and consumption monitoring.

## Reliable

- Durable NRTL-certified NEMA type 3R enclosure
- Five-year warranty



**LISTED**

To learn more about Enphase offerings, visit [enphase.com](https://enphase.com)



# Enphase IQ Combiner

## MODEL NUMBER

IQ Combiner X-IQ-AM1-240-B	IQ Combiner with Enphase IQ Envoy™ for integrated revenue grade PV production metering (ANSI C12.20 +/- 0.5%) and optional consumption monitoring (+/- 2.5%).
----------------------------	---

## ACCESSORIES (order separately)

Enphase Mobile Connect™ CELLMODEM-01 (3G) CELLMODEM-03 (4G)	Plug and play industrial grade cellular modem with five-year data plan for systems up to 60 microinverters. (Available in the US, Canada, Mexico, Puerto Rico, and the US Virgin Islands, where there is adequate cellular service in the installation area.)
Consumption Monitoring CT CT-200-SPLIT	Split core current transformers enable whole home consumption metering (+/- 2.5%).

## ELECTRICAL SPECIFICATIONS

Rating	Continuous duty
Solar branch circuit breakers	Three 2-pole 20A/240 VAC DIN rail-mounted breakers
Maximum system voltage	240 VAC
Rated output current	48 A
Rated input current, each input	16 A
Maximum fuse/circuit breaker rating (output)	60 A
Production Metering CT	200A solid core pre-installed on solar busbar and wired to IQ Envoy

## MECHANICAL DATA

Dimensions (WxHxD)	38.0 x 38.7 x 20.3 cm (15.0" x 15.3" x 8.0")
Weight	5.1 kg (11.2 lbs)
Ambient temperature range	-40° C to +46° C (-40° to 115° F)
Cooling	Vented, natural convection, plus heat shield
Enclosure environmental rating	Outdoor, NRTL-certified, NEMA type 3R, polycarbonate construction
Wire size	14 to 6 AWG copper conductors for branch inputs. 14 to 4 AWG copper conductors for combined output. Follow local code requirements for conductor sizing.
Altitude	To 2000 meters (6,560 feet)

## INTERNET CONNECTION OPTIONS

Integrated Wi-Fi	802.11b/g/n
Ethernet	802.3, Cat5E (or Cat 6) UTP Ethernet cable - not included
Cellular	Optional, CELLMODEM-01 (3G) or CELLMODEM-03 (4G) - not included

## COMPLIANCE

Compliance, Combiner	UL 1741
Compliance, IQ Envoy	UL 916 CAN/CSA C22.2 No. 61010-1 47 CFR, Part 15, Class B, ICES 003 IEC/EN 61010-1:2010, EN50065-1, EN61000-4-5, EN61000-6-1, EN61000-6-2 Metering: ANSI C12.20 accuracy class 0.5

To learn more about Enphase offerings, visit [enphase.com](http://enphase.com)

© 2017 Enphase Energy. All rights reserved. All trademarks or brands in this document are registered by their respective owner.  
2017-03-15

