

# XLPE/USE-2/RHH/RHW-2



Product Description: Single-conductor wire, insulated with XLPE, sunlight resistant, rated at 90°C wet or dry, 600V, 1000V

*Made in the U.S.A.*

Standard Color - Black  
Voltage 600/1000V  
Temperature – 40°C to 90°C



UL Standard 44  
Issue Number 16  
July 15, 2005

## Construction:

Single conductor cross-linked polyethylene Type USE-2, flame retardant, VW-1 moisture resistant, RoHS, sunlight resistant, temperature rating 90°C wet or dry, -40°C cold. Suitable for conduit and raceways installed underground in conduit.

P/N	AWG	STRAND	INS THICKNESS	NOM DIA.	APPROX WEIGHT
0225USE	14	7/BC	.045	.160	18
0215USE	12	7/BC	.045	.180	29
02122USE	10	7/BC	.045	.205	44
02119USE	8	7/BC	.060	.270	75
02131USE	6	7/BC	.060	.309	105
02132USE	4	7/BC	.060	.357	159
TBD	2	7/BC	.060	.419	242

These values are nominal in accordance with industry standards. Additional gauges, tinned copper or flexible stranding are available upon request. Additional colors available with sunlight resistance approval.

## UL Standards

USE, USE-2 600V per UL854  
RW-90 1000V Per UL44 CSA C 22.2 No 38  
RHH, RHW, RHW-2 PER UL44  
USE & USE-2 – Rated for direct burial and underground duct services per UL854

Vertical flame and FT-1 per UL1581, Section 1060  
XENON-ARG test per 1580, Section 1200  
Flexibility at low temperature per UL1581, Section 583

## Electrical Testing

Spark test at:  
10,000V RMS 14-10 AWG  
12,500V RMS 8-2 AWG  
Dielectric test potential:  
6,000V RMS 14-10 AWG  
7,500V RMS 8-2 AWG  
in accordance with UL44  
Continuity test per UL44

5/26/09-added AWG's 6-2, updated Electrical Testing  
1/7/10-added CSA to RW90 & direct burial per UL854



FALCON FINE WIRE AND WIRE PRODUCTS, INC.  
2401 DISCOVERY BLVD • ROCKWALL, TEXAS 75032  
214-771-3441 • 972-722-9168 • falconwire@aol.com

