

Quick Rack™ Approved Modules

Patented Rail-Free Mounting System for Composition/Asphalt Shingle Roofs

Evaluated and Approved Modules for use with Quick Rack per ANSI/UL 2703 Edition 1 Modules load tested at 50 PSF downward, 35 PSF upward, 23.4 PSF down-slope and grounding/bonding tested	Model Dimensions			Maximum Allowable Module Cantilever	
	length (mm)	width (mm)	thickness (mm)	landscape (in)	portrait (in)
LG Solar Mono X, Mono X Ace & Mono X NeON 35mm	1640	1000	35	17.7	2.7
LGXXS1C-G3, LGXXS1C-A3, LGXXS1C-B3, LGXXS1K-G3, LGXXS1K-A3, LGXXS1K-B3, LGXXN1C-G3, LGXXN1C-A3, LGXXN1C-B3, LGXXA1C-B3					
LG Solar Mono X, Mono X Ace & Mono X NeON 40mm	1640	1000	40	13.7	2.7
LGXXS1C-G4, LGXXN1K-G4, LGXXN1C-G4, LGXXA1C-G4					
Trina Solar	1650	992	35	14.2	7.8
TSM-XXX-PA05.05, TSM-XXX-PA05.08, TSM-XXX-PD05.05, TSM-XXX-PD05.08					
Yingli Solar YGE 60 Cell	1650	990	35	7.8	7.8
YLXXP-29b 35mm					
Suniva Optimus Series 40mm	1652	982	40	7.8	n/a
Black OPT XXX-60-4-1B0, Silver OPT XXX-60-4-100					
Suniva Optimus Series 35mm	1660	990	35	14	n/a
Black OPT XXX-60-4-1B0, Black OPT XXX-60-4-1B1, Silver OPT XXX-60-4-100, Silver OPT XXX-60-4-101					
Renesola 156 Series, Clarus, Virtus, & Virtus II	1640	992	40	15.1	8.8
JCXXS-24/Bb, JCXXF-24/Bb-b, JCXXS-24/Bb-b, JCXXM-24/Bb, JXXM-24/Bbv, JCXXM-24/Bb, JCXXM-24/Bbh					
Hyundai Solar RG-Series	1640	998	35	14.1	7.8
HiS-MXXXRG, HiS-SXXXRG					
Hyundai Solar MF-Series	1476	983	35	12.5	7.7
HiS-SXXXMF					
Hyundai Solar MG Series	1645	983	35	14.2	7.7
HiS-MXXXMG, HiS-SXXXMG					
SolarWorld Sun Module Pro Poly & Plus Mono	1675	960	33	14.5	7.8
SWXXX POLY, SWXXX-MONO, SWXXX-MONO BLACK					

Note: Module wattage is represented by XXX in product codes.

Approved Modules Continued

Evaluated and Approved Modules for use with Quick Rack per ANSI/UL 2703 Edition 1 Modules load tested at 50 PSF downward, 35 PSF upward, 23.4 PSF down-slope and grounding/bonding tested	Model Dimensions			Maximum Allowable Module Cantilever	
	length (mm)	width (mm)	thickness (mm)	landscape (in)	portrait (in)
Axitec AXI Power, Premium, & Plus SE	1640	992	40	13.7	9.8
AC-XXXP/156-60S, AC-XXXM/156-60S, AC-XXXM/156-60S, AC-XXX-P/156-60S, AC-XXXM/156-60S					
Winaico WST-P6 Series	1665	999	35	14.4	n/a
WST-XXXP6					
Phono Solar Diamond & Onyx Series	1641	993	40	13.7	7.8
PSXXXP-20/U, PSXXXM-20/U, PSXXXP-20/U, PSXXXM-20/U					
Canadian Solar	1638	982	40	11-19.7*	n/a
CS6P-XXXP, CSP-XXXP-SD					
Canadian Solar	1650	992	40	11-19.7*	n/a
CS6K-XXXM, CS6K-XXXM All Black					
Evaluated and Approved Modules for use with Quick Rack per UL SUB 2703 Issue 1 Modules load tested at 30 PSF downward, 30 PSF upward and grounding/bonding tested	Model Dimensions			Maximum Allowable Module Cantilever	
	length (mm)	width (mm)	thickness (mm)	landscape (in)	portrait (in)
BenQ Green Triplex	1639	983	40	14.9	9.7
PM060M02-XXX, PM060P00-XXX, PM245P00-XXX, PM250M01-XXX, PM245P03-XXX					
ET Solar	1640	992	40	14.1	n/a
ET-PXXXBB, ET-PXXXWW/WB, ET-MXXXWW, ET-PXXXWWG					
Yingli Solar YGE 60 Cell	1650	990	40	7.8 - 17.7*	7.8
YLXXXP-29b 40mm					
Hanwha Solar HSL 60 & HSL 72	1636	988	40	15.5	9.8
HSL60P6-PB-0-XXXT, HSL60P6-PB-0-XXXTW, HSL60P6-PB-0-XXXTB, HSL60P6-PB-4-XXXT, HSL60P6-PB-4-XXXTW, HSL60P6-PB-4-XXXTB, HSL60P6-PB-1-XXX, HSL60P6-PB-1-XXXB					
Canadian Solar	1638	983	40	11-19.7*	6.7-7.8*
CS6P-XXXM, CS6P-XXXM All Black					

Note: Module wattage is represented by XXX in product codes.

*See manufacturer's instructions for location/load specific cantilever values.



925-478-8269 | 2700 Mitchell Dr. | Walnut Creek, CA 94598
www.quickmountpv.com | sales@quickmountpv.com