



samlexamerica®

4A



DC-DC Step Up Converter

Model
IDC-100A-24
4 Amps

Design Features

- Fully isolated
- Short circuit protected
- Current limited

2 YEAR WARRANTY

MODEL NO.		IDC-100A-24
INPUT	INPUT VOLTAGE RANGE	9 -18 VDC
	OUTPUT VOLTAGE	24.5 VDC
	OUTPUT CURRENT	4 A
	INPUT TO OUTPUT ISOLATION	Yes. > 400 V RMS
	OUTPUT RIPPLE & NOISE	< 50 mV RMS
	PEAK EFFICIENCY	85%
	COOLING	By temperature controlled fan
	OPERATING TEMPERATURE	-20°C to +30°C, De-rate linearly to zero at 70°C
	HUMIDITY (Non-condensing)	Max 95%
FUSE SPECIFICATIONS	EXTERNAL INPUT SIDE FUSE (Inline with "input +" terminal)	32V, 15A
	EXTERNAL OUTPUT SIDE FUSE (Inline with "output +" terminal)	32V, 5A
	PROTECTIONS	Overload / short circuit on the output side, over voltage on the output side, over voltage / transients on the input side, reverse polarity on the input side, over heating
WIRE SIZE	INPUT WIRE (Up to 6 ft)	AWG #8
	OUTPUT WIRE (Up to 10 ft)	AWG #12
SAFETY & EMC	EMISSION	EN50081-1 / EN61000-6-3
	IMMUNITY	EN50082-1 / EN61000-6-1
	AUTOMOTIVE	95 / 54 / EC
GENERAL	INPUT / OUTPUT CONNECTIONS	Quick connect male 6.3mm / ¼" flat blade
	DIMENSIONS, MM (L x W x H)	151 x 88 x 50
	DIMENSIONS, INCHES (L x W x H)	5.9 x 3.5 x 1.9
	WEIGHT, KG	0.5
	WEIGHT, LB	1.2

NOTE: Specifications are subject to change without notice

12004-IDC-100A-24-0315

To view a full selection of Samlex products visit our website at www.samlexamerica.com or contact us: 1-800-561-5885 or sales@samlexamerica.com