

D221NRB

Safety Switch , 30A, Fusible, Cartridge (Class H, K or R), 2-Pole



by Schneider Electric

List Price \$188.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Terminal Type	Lugs
Type of Duty	General Duty
Maximum Voltage Rating	240VAC
Wire Size	#14 to #8 AWG(Al/Cu)
Depth	3.75 Inches
Height	9.63 Inches
Width	7.25 Inches
Action	Single Throw
Ampere Rating	30A
Approvals	UL Listed File: E2875
Enclosure Rating	NEMA 3R
Enclosure Type	Rainproof and Sleet/Ice proof (Indoor/Outdoor)
Enclosure Material	Galvannealed Steel
Factory Installed Neutral	Yes
Fuse Type	Cartridge (Class H, K or R)
Disconnect Type	Fusible
Short Circuit Current Rating	100kA (max. depending on fuse type)
Mounting Type	Surface
Number of Poles	2-Pole

Shipping and Ordering

Category	00106 - Safety Switch, General Duty, 30 - 200 Amp, NEMA3R
Discount Schedule	DE1A
GTIN	00785901460589
Package Quantity	1
Weight	4.82 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 06/30/2010 15:18:52