

D324NRB

Safety Switch , 200A, Fusible, Cartridge (Class H, K or R), 3-Pole



List Price \$1,461.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

Terminal Type	Lugs
Type of Duty	General Duty
Maximum Voltage Rating	240VAC
Wire Size	#2 to 300 AWG/kcmil(Al) - #4 to 300 AWG/kcmil(Cu)
Depth	8.25 Inches
Height	29.25 Inches
Width	17.25 Inches
Action	Single Throw
Ampere Rating	200A
Approvals	UL Listed File: E2875
Enclosure Rating	NEMA 3R
Enclosure Type	Rainproof and Sleet/Ice proof (Indoor/Outdoor)
Enclosure Material	Galvannealed Steel
Factory Installed Neutral	Yes
Fuse Type	Cartridge (Class H, K or R)
Disconnect Type	Fusible
Short Circuit Current Rating	100kA (max. depending on fuse type)
Mounting Type	Surface
Number of Poles	3-Pole

Shipping and Ordering

Category	00106 - Safety Switch, General Duty, 30 - 200 Amp, NEMA3R
Discount Schedule	DE1A
GTIN	00785901461524
Package Quantity	1
Weight	45.33 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	US

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.