

QO24L70RB

Load Center , 70A, Fixed - Factory installed main lugs, 120/240VAC



by Schneider Electric

List Price \$131.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

| | |
|---------------------------------|---|
| Ampere Rating | 70A |
| Application | Designed to meet residential, commercial and industrial requirements to protect electrical systems, equipment and people. |
| Maximum Tandem Circuit Breakers | 2 |
| Approvals | UL Listed |
| Cover Type | Surface |
| Bus Material | Tin Plated Aluminum |
| Enclosure Type | Outdoor/Rainproof |
| Box Number | 1R |
| Enclosure Rating | NEMA 3R |
| Grounding Bar | Order separately |
| Short Circuit Current Rating | 10kA |
| Main Type | Fixed - Factory installed main lugs |
| Maximum Single Pole Circuits | 4 |
| Voltage Rating | 120/240VAC |
| Wire Size | #12 to 3 AWG(Al) - #14 to 4 AWG(Cu) |
| Wiring Configuration | 3-Wire |
| Phase | 1-Phase |
| Depth | 4.00 Inches |
| Height | 9.38 Inches |
| Width | 4.88 Inches |
| Spaces | 2 |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 00101 - Load Centers, 1 Phase, NEMA1 & 3R, 2 - 8 Circuit, Type QO |
| Discount Schedule | DE3A |
| GTIN | 00785901785132 |
| Package Quantity | 1 |
| Weight | 5 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |
| Country of Origin | MX |

Generated: 07/14/2010 18:00:45

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 07/14/2010 18:00:45