QO612L100DS

Load Center , 100A, Fixed - Factory installed main lugs, 120/240VAC



List Price \$90.00 USD

Availability Stock Item: This item is normally stocked in our distribution facility.

Technical Characteristics

Ampere Rating	100A
Maximum Single Pole Circuits	12
Application	Designed to meet residential, commercial and industrial requirements to protect electrical systems, equipment and people.
Approvals	UL Listed
Cover Type	Surface (with door)
Bus Material	Tin Plated Aluminum
Enclosure Type	Indoor
Box Number	4
Enclosure Rating	NEMA 1
Grounding Bar	Order separately
Short Circuit Current Rating	10kA
Main Type	Fixed - Factory installed main lugs
Voltage Rating	120/240VAC
Wire Size	#8 to 1 AWG(Al/Cu)
Maximum Tandem Circuit Breakers	6
Phase	1-Phase
Wiring Configuration	3-Wire
Depth	3.80 Inches
Height	12.57 Inches
Width	8.88 Inches
Spaces	6
Ampere Rating	100A
Maximum Single Pole Circuits	12
Application	Designed to meet residential, commercial and industrial requirements to protect electrical systems, equipment and people.
Approvals	UL Listed
Cover Type	Surface (with door)
Bus Material	Tin Plated Aluminum
Enclosure Type	Indoor
Box Number	4
Enclosure Rating	NEMA 1
Grounding Bar	Order separately
Short Circuit Current Rating	10kA
Main Type	Fixed - Factory installed main lugs
Voltage Rating	120/240VAC
Wire Size	#8 to 1 AWG(Al/Cu)
Maximum Tandem Circuit Breakers	6

Generated: 06/08/2010 17:04:00



Phase	1-Phase
Wiring Configuration	3-Wire
Depth	3.80 Inches
Height	12.57 Inches
Width	8.88 Inches
Spaces	6

Notes:

70A (max) branch circuit breaker and 70A (max) back fed main circuit breaker.

Shipping and Ordering

Category	00101 - Load Centers, 1 Phase, NEMA1 & 3R, 2 - 8 Circuit, Type QO
Discount Schedule	DE3A
GTIN	00785901785620
Package Quantity	1
Weight	8.29 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

